

SUPERPLASMA PL HI VIZ CE KASK

WHE00109

EN



TECHNICAL DETAILS



MATERIAL

EXTERNAL SHELL:
HD Polypropylene

INTERNAL SHELL:
HD Expanded Polystyrene

HEADBAND:
Soft PA Nylon



STANDARD

EN 12492



TEMPERATURE OF USE

-20°C / +35°C



SIZE

Universal-adjustable
from 51 to 62 cm



WEIGHT

420 g



CATEGORY

II



WHE00109-201
WHITE



WHE00109-210
BLACK



WHE00109-221
YELLOW FLUO



WHE00109-223
RED FLUO



WHE00109-224
LIME FLUO

TECHNOLOGIES



UP & DOWN SYSTEM

A size adjustment system comprised of three components for all-day comfort. A central dial allows easy size adjustments, and side wings ensure a snug fit against the back of the head. The patented Up & Down hinge with helmet stability technology adapts as the wearer moves to deliver a more secure and personalized fit.



ANTI-INTRUSION MESH

Metal mesh vent covers that prevent debris from entering the ventilation channels while maintaining breathability.



2DRY LINER

A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



VENTILATION CHANNELS

Designed with 10 air intakes and internal channels for enhanced breathability and wearer comfort.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



VISOR ATTACHMENT POINTS

Helmet designed with attachment points for securing KASK eye protection accessories.



EARMUFF ADAPTER ATTACHMENT POINTS

Helmet designed with attachment points for earmuff adapters.



INTEGRATED LAMP CLIPS

Designed with 4 built-in, nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.



HI VIZ DETAILS

High visibility color shell, luminescent lamp clips and high visibility reflective adhesives for added safety in low visibility conditions.

PERFORMANCES

Protection against top impacts	K	5 kg from 2 m 100 J	Chinstrap release	K	>50 kg
Protection against side, front and rear impacts	K	5 kg from 0,5 m 25 J	Retention system effectiveness	K	
Protection against the penetration of objects	K	3 kg from 1 m 30 J			

K EN 12492 standard requirements

ADDITIONAL INFORMATION

3 10
YEARS GUARANTEE YEARS SHELF LIFE

SHELF LIFE

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

GUARANTEE

3 years starting from the date of purchase.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

SAFETY ACCESSORIES



WV100018
VISOR V2 PLUS



WV100024
FACE SHIELD



WV100003
VISOR FULL FACE



WV100006
MESH VISOR



WHP00004/5/6
EARMUFFS



WLA00001/2/3
HEADLAMPS



WPA00007
WINTER CAP



WAC00020/24
NECK SHADE



WAC00032/33
NECK SHIELD RW



WAC00036/37
SUN SHIELD

DISCOVER MORE



SCAN FOR
COMPLETE
COLLECTION